

PRODUCT DESCRIPTION

BF MYLAR is a polyester film designed to be used as a transfer media for printable heat transfer vinyl. Once the protective layer has been removed, BF Mylar needs to be applied to the printed film. Avoid creating air bubbles during this process.

We recommend following the instructions related to the printable film used with BF MYLAR.

TECHNICAL DATA



Film: PET/polyester



Thickness: 100μ (±5%)



Liner: adhesive PET



Finish: gloss

APPLICATION STEPS

- Remove the protective film
- Apply BF MYLAR to the printed material, manually or using a laminating machine. Make sure to avoid the formation of air bubbles
- Remove the carrier from the printed media
- Position the design on the garment
- Apply to the garment using the settings indicated in the printable film's spec sheet
- Remove BF MYLAR as indicated in the spec sheet of the printed film

APPLICATION



Temperature: See spec sheet for the printable media being used



Liner removal: See spec sheet for the printable media being used

Comply with
regulation **REACH**
n°1907/2006/EU

SIZES

H 50 cm L 20 mt

H 75 cm L 20 mt

H 100 cm L 20 mt

H 150 cm L 20 mt

SAFETY NOTICE

The values reported in this document are average values as tested under normal conditions in our lab. We cannot provide a guarantee regarding the information above mentioned in this page. Due to possible variations in the production of garments, B-FLEX recommends testing the material prior to all applications. Rev_2021/03

follow us

HEADQUARTERS B-FLEX ITALIA S.r.l. info@b-flexitalia.com | www.b-flexitalia.com

NORTH AMERICA BRANCH B-FLEX AMERICA LLC info@b-flexamerica.com | www.b-flexamerica.com

ASIA-PACIFIC BRANCH B-FLEX PACIFIC PTY LTD info@b-flexpacific.com | www.b-flexpacific.com



BF MYLAR
PRINT&CUT



- *Highly adhesive*
- *Easy to work*
- *Works with all digital printing films*